



Spot Type Liquid Leakage Detector



The Sensaphone FGD-L8215 Spot Type Liquid Leakage Detector is used to detect the presence of liquid on a horizontal surface. High Voltage and Current Rating of the Dry Contact Relay Output allow FGD-L8215 Spot Type Liquid Leakage Detector to control electrical solenoid water valve directly. Green LED indicates the power of the device is on while Blinking Red LED indicates the detection of liquid.

TECH SPECS

Dimensions:	57 x 47 x 39 mm (without the sensing probes)
Weight:	125 g
Housing:	Grey plastic
Power Requirement:	12 – 24V DC
Max. Current Consumption:	65 mA
Output:	Normally energized relay Dry contact output (Normally Closed / Normally Open)
Max. Output Power Rating:	250V AC, 1 A
Recognition Time:	5 Seconds
Sensing Probes:	- Package comes with a pair of “L” shape conductive electrode probes which can be setup into two different detection height levels by different orientation. - Can be replaced with most of the water sensing cables in the market.
Compatibility:	Compatible with major streams of Sensaphone monitoring systems

All specifications subject to change without notice

Product Name

Part Number

Spot Type Liquid Leakage Detector FGD-L8215



Family owned and made in the USA since 1985

901 Tryens Road
Aston, PA 19301

Phone: 877-373-2700
Web: sensaphone.com

