

SENSAPHONE Monitoring Sensor

WSG30 Wireless Sensors

WSG Wireless Dry Contact Sensor



Description

The WSG Wireless Dry Contact sensor is designed to work exclusively with the Sensaphone WSG30. This sensor includes a built-in radio transmitter and input terminals for connecting to any normally-open or normally closed output. (Use of this device with solid-state outputs is not recommended.) The sensor comes with two AA alkaline batteries which will power the sensor for up to two years. An optional plug-in power supply is also available. The batteries then become a backup if main AC power fails.

Package Contents

- (1) WSG Wireless Dry Contact Sensor
- (2) AA Alkaline batteries
- (1) Mounting kit

Specifications

Operating Temperature Range:
32° to 122°F (0° to 50°C)

Operating Humidity Range:
0–95%

Input Characteristics:
3MΩ To 3V

Range:
Up to 300' (90m)

Power Requirements:
(2) AA Batteries / 5VDC Power Supply (Router Mode)

Wireless Technology:
ISM 2.4GHz, 100 mW (20dBm)

Housing:
White plastic

Size:
3.1" x 3.8" x 1.1"
7.9cm x 9.8cm x 2.85cm

Compatibility:
WSG30

**Specifications subject to change without notice*

WSG Wireless Dry Contact SensorFGD-WSG30-DRY
5V Power Supply XFR-0041