



# WIRELESS TEMPERATURE DISPLAY WITH BUFFERED TEMPERATURE SENSOR



## Buffer temperature fluctuations

The Wireless Temperature Display is used exclusively with the Sensaphone WSG30 to provide an at-a-glance reading of the current temperature wherever the display is installed. By placing the included probe in a bottle filled with glycol, users will receive a reading that represents the temperature of the contents of inside of the refrigerator rather than the ambient air temperature. The external probe is wired to the display with the included 12' of wire.

Name	Temperature Sensor in Glass Bead Vial
Sensor Temperature Range	-20° to 176°F   -28° to 80°C
Accuracy	± 1°F   ±.56°C
Wireless Range	300'   90m
Connection	WSG Wireless
Housing	Plastic
Dimensions	4.65" x 3.7" x 1.1"   118 x 94 x 28mm
Notes	(2) AA alkaline batteries will power sensor for 2 years

All specifications subject to change without notice

### Product Name

### Part Number

WSG Temperature Display with Glycol Vial. . . . . FGD-WSG30-LCDGLY  
 WSG Temperature Display with Glycol Vial w/NIST Certification . . . . . FGD-WSG30-LCDGLYN



Family owned and made in the USA since 1985

901 Tryens Road  
Aston, PA 19301

Phone: 877-373-2700  
Web: sensaphone.com

