



WIRELESS TEMPERATURE DISPLAY WITH 1" RTD PROBE

Wireless Temperature Sensing

The Wireless Temperature Display is used exclusively with the Sensaphone WSG30 and paired with a 1" RTD temperature probe to provide an at-a-glance reading of the current temperature wherever the probe is installed. The display is ideal for any location where onsite staff need a quick, convenient visual reading of the sensor, saving them the time of checking the monitoring system's data.



TECH SPECS

Name	Wireless temperature display with 1" RTD Probe
Sensor Temperature Range	-328° to 399°F -200° and 204°C
Accuracy	± 1°F ±.56°C
Wireless Range	300' 90m
Connection	WSG Wireless
Housing	Plastic
Dimensions	4.65" x 3.7" x 1.1" 118 x 94 x 28mm
Notes	(2) AA alkaline batteries will power sensor for 2 years

All specifications subject to change without notice

Product Name

Part Number

WSG Temperature Display with 1" RTD Probe	FGD-WSG30-LCDR1
WSG Temperature Display with 1" RTD Probe w/NIST.	FGD-WSG30-LCDR1N



Family owned and made in the USA since 1985

901 Tryens Road
Aston, PA 19301

Phone: 877-373-2700
Web: sensaphone.com

